

## 2/16 AWG Speaker Cable KT1603



---


### *Construction Parameters:*

Conductor Stranded	16 AWG (19×29) Bare Copper
No. of Conductor	2
Nom. Insulation Thickness	0.010"/0.25mm PVC CMR
Nom. Jacket Thickness	0.017"/0.43mm PVC CMR
Overall Cable Diameter	0.182"/4.62mm PVC CMR
Approximate Cable Weight	24.4 Lbs/1000ft
Flame Rating	UL 1666 Riser Flame Test

---

### *Electrical Characteristics:*

Nom. D.C. R. Resistance @ 20°:	4.4 ohms per 1000ft
Temperature Rating	-20° C to 60° C
Operating Voltage	300 V RMS Max
Capacitance Between Conductors@1KHz	33 pF/ft Nom.
Insulation Colors	Black, Red
Jacket Colors	Grey, Black, Brown, White
RoHS	YES



---

### *Order Informations:*

Marking	KINGTONE KT1603 2/16 AWG SPEAKER CABLE XXX M/FT
Package	500FT/Pull Box, 1000FT/Wooden Spool, Pallet
Delivery time	Normally 15 days after received the deposit.

---

### *Online Service:*

Skype	kingtone3
ICQ	246632889

---