

Speaker Cable

KT1600

KINGTONE
ELECTRONICS

Applications:

For use as a signal wire connecting amplifier and speakers in an audio system.

Conductors:

Two bare copper conductors; two bare copper clad aluminum conductors; one bare copper and one tinned copper; one bare copper clad aluminum and one tinned copper clad aluminum.

Construction Parameters:

RED/BLACK

Section(mm²)

Conductor

2×0.35

31x0.12mm OFC wires

2×0.50

44x0.12mm OFC wires

2×0.75

66x0.12mm OFC wires

2×1.00

13x7x0.12mm OFC wires

2×1.50

19x7x0.12mm OFC wires

2×2.00

25x7x0.12mm OFC wires

2×2.50

32x7x0.12mm OFC wires



Construction Parameters:

Transparent

Section(mm²)

Conductor

2×0.35

31x0.12mm OFC wires

2×0.50

44x0.12mm OFC wires

2×0.75

66x0.12mm OFC wires

2×1.00

13x7x0.12mm OFC wires

2×1.50

19x7x0.12mm OFC wires

2×2.00

25x7x0.12mm OFC wires

2×2.50

32x7x0.12mm OFC wires



Order Informations:

Marking

KINGTONE KT1600 SPEAKER CABLE XXX M/FT

Package

500FT/Pull Box, 1000FT/Wooden Spool, Pallet

Delivery time

Normally 15 days after received the deposit.

