

## RG 178 FEP Coaxial Cable

KT0406

---

### Construction Parameters:

Inner Conductor	7×0.004"/7×0.102mm Silver Plated Copper Clad Steel
Dielectric	0.035"/0.88mm FEP
Shield	Nom. 0.051"/1.30mm Silver Plated Copper Clad Steel
Jacket	0.072"/1.83mm FEP (Color by your choise)

---

### Electrical Characteristics:

Capacitance	96.45 pF/m	29.5 pF/ft
Impedance	50 Ω	
Velocity of Propagation	0.7	
Max Operating Voltage(KVMS)	0.75	
Operating Temp Range (PVC)	-55 °C to 200 °C	
RoHS	YES	



---

### Attenuation(20 °C):

Frequency (MHZ)	Max Attenuation (dB/100m)
100	45.30
400	91.20
1000	146.00
3000	265.00

---

### Order Informations:

Marking	KINGTONE KT0406 RG 178 FEP COAXIAL CABLE XXX M/FT (or Per customer's request)
Package	100m/Roll, 100m/Spool,305m/1000ft/Spool/Pallet (or Per customer's request)
Delivery time	Normally 15 days after received the deposit.
More informations	please contact with us.

---

### Online Service:

Skype	kingtone3
ICQ	246632889

---